

ORION GN&C DETECTION AND MITIGATION OF PARACHUTE PENDULOSITY

Mark A. Kane,^{*} Roger Wacker[†]

New techniques being employed by Orion guidance, navigation, and control (GN&C) using a reaction control system (RCS) under parachutes are described. Pendulosity refers to a pendulum-oscillatory mode that can occur during descent under main parachutes and that has been observed during Orion parachute drop tests. The pendulum mode reduces the ability of GN&C to maneuver the suspended vehicle resulting in undesirable increases to structural loads at touchdown. Parachute redesign efforts have been unsuccessful in reducing the pendulous behavior necessitating GN&C mitigation options. An observer has been developed to estimate the pendulum motion as well as the underlying wind velocity vector. Using this knowledge the control system maneuvers the vehicle using two separate strategies determined by a wind velocity magnitude threshold; at high wind velocities the vehicle is aligned with the wind direction and for cases with lower wind velocities the vehicle is aligned such that it is perpendicular to the swing plane. Pendulum damping techniques using RCS thrusters are discussed but have not been selected for use onboard the Orion spacecraft. The techniques discussed in this paper will be flown on Exploration Mission 1 (EM-1).

^{*} Control Engineer, NASA-JSC Aerosciences and Flight Mechanics Division, 2101 NASA Pkwy, Houston TX 77058

[†] Orion GN&C Lead, Lockheed Martin Corporation, M/S H3B, P.O. Box 58487, Houston TX 77258